

Audrey

A4 II Series**Touch POS Terminal****FEATURES**

- Sleek and modern design
- All-in-one POS terminal with 15" PCAP display
- Fanless, high-performance Intel CPU (Meteor & Alder Lake)
- Entire unit IP54 certified, front panel IP65
- Available with dual M.2 PCIe SSD storage
- DDR4/DDR5 memory options
- Windows 11 IoT Enterprise and Linux Ubuntu 22.04

Audrey

Specifications



Item	A4-2-M	A4-2-N
Size	15"	
Aspect Ratio	4:3	
Resolution	1024 x 768	
Brightness	400 nits	
Touch	PCAP multi-touch display with anti-glare	
CPU	Meteor Lake Intel® Core™ Ultra 5 125U Intel® Core™ Ultra 7 155U	Alder Lake-N Intel® Processor N95 Intel® Processor N97 Intel® Core™ i3-N305
Memory	DDR5: 8GB, 16GB, 32GB, 48GB	
Storage	2 x M.2 PCIe SSD: 128GB / 256GB / 512GB / 1TB (supports RAID)	1 x M.2 PCIe SSD: 128GB / 256GB / 512GB / 1TB
I/O Ports	2 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2) 1 x Intel LAN (IEEE 802.3 10/100/1000/2500 Mbps) 1 x RJ11 port support for 2 cash drawers with 24V / 12V jumper setting 1 x DC +12V out 5 x USB 3.2 1 x DC + 12V input 1 x audio (1 x line-out) 1 x HDMI 1 x Type-C (data transfer / display / power delivery 60W) 1 x Type-C (Data transfer)	
Expansion I/O Options	1 x 12V & 1 x 24V powered USB 2 x serial ports, RS-232 (RJ45), 0V/5V/12V selection by BIOS (COM3, COM4) 2 x USB 2.0 1 x serial port, RS-232 (DB9), 0V/5V/12V selected in BIOS (COM3)	
Speaker	1 x speaker (3W)	
Peripheral Options	MSR, EMV reader, fingerprint reader, RFID/ NFC reader 10" USB 2nd display, 15" HDMI 2nd display 2D barcode scanner, camera, I/O expansion boxes EX-100 & EX-101 (only A base), EX-300, cash drawer	
Mounting	75 x 75 VESA	
Stand	A-base (standard), PS-103 Cosmo printer stand (compatible with RP-700 or Epson TM-T70 II)	
Wireless Option	Intel AX210 Wi-Fi 6E (supports IEEE 802.11 a/b/g/n/ac/axR2) BT 5.3	
Display Support	3 independent displays (main display + HDMI + Type-C)	
Spill & Dust Resistant	Entire unit IP54 certified, front panel IP65	
Operating System	Windows 11 IoT Enterprise LTSC 24H2 (64bit) Linux Ubuntu 24.04	
TPM & vPro	1. Intel vPro	S/W TPM 2.0 (BIOS)
Power Adaptor	AC in 100 to 240V, DC out 12V, 90W (standard) / 180W (with powered USB)	AC in 100 to 240V, DC out 12V, 65W (standard) / 180W (with powered USB)
Reliability	System operating temperature: 0~40°C / 32~104°F System humidity: 15% ~ 80% Storage temperature: -20~60°C / -4~140°F	
Dimensions (W x H x D)	330 x 340 x 201 mm / 12.99 x 13.39 x 7.91 in	
Weight	6.2 kg / 13.67 lb	
Warranty	5 years	

*Specification is subject to change without prior notice

Contact Us

Partner Tech USA Inc.
 1255 N. Patt Street
 Anaheim, CA 92801
 Phone: 949-598-1888
sales@partnertechcorp.com

Partner Tech Mexico & Latin America
 Blvd. Palmas Hills 1, Piso 8, Valle de las Palmas, Huixquilucan
 Ciudad de México, 52764, Mexico
 Phone: 949-598-1888
info@partnertechcorp.com

