

Audrey

A5 Series**Touch POS Terminal**

FEATURES

- Sleek & modern design
- All-in-one POS with 15.6" PCAP display
- Latest, high-performance Intel CPU with fanless design
- Front panel IP65, whole device IP54 certified
- High speed M.2 PCIe SSD
- Supports Windows 10/11 and Linux Ubuntu

Audrey

Specifications



Item	A5-1-AL	A5-1-E	A5-1-K
Size	15.6"		
Aspect Ratio	16:9		
Resolution	1366 x 768 / 1920 x 1080 (option)		
Brightness	220 nits / 400 nits (option)		
Touch	PCAP touch		
CPU	Alder Lake-P Intel® Celeron® 7305 Intel® Core™ i3-1215U Intel® Core™ i5-1245U, vPro Intel® Core™ i7-1265U, vPro	Elkhart Lake Intel® Celeron® J6412	Kaby Lake-U Intel® Core™ i3-7100U Intel® Core™ i5-7300U
Memory	DDR4 4GB, 8GB, 16GB, 32GB		
Storage	M.2 PCIe SSD: 128GB / 256GB / 512GB		
I/O Interface	3 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2, COM3) 1 x Intel LAN (IEEE 802.3 10/100/1000 Mbps) 1 x RJ11 port support for 2 cash drawers with 24V/12V jumper setting 1 x DC + 12V out 4 x USB 3.2 + 2 x USB 2.0 1 x DC + 12V input 1 x audio (1 x line-out) 1 x HDMI 1 x Type-C (data transfer + display)		2 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2) 2 x LAN (IEEE 802.3 10/100/1000 Mbps) 4 x USB 3.0 + 2 x USB 2.0
Speaker	1 x speaker (3W)		
Peripheral Options	MSR, EMV reader, fingerprint reader, RFID/NFC, VFD, USB 2nd display, HDMI 2nd display, 2D barcode scanner, camera, IO extension box (EX100, EX101, EX300), cash drawer, PS-103 Cosmo printer stand (space-saving stand, compatible with RP-700 or Epson TM-T70 II)		
Wireless (option)	Wi-Fi 6E Intel AX210, IEEE 802.11 a/b/g/n/acR2/axR2 BT 5.2		
Display Support	3 independent displays (main display + HDMI + Type-C)		2 independent displays (main display + HDMI)
Spill & Dust Resistant	Entire unit IP54 certified, front panel IP65-rated		
Operating System	1. Windows 11 IoT Enterprise GAC (64bit) ready 2. Windows 10 IoT Enterprise LTSC 21H2 (64bit) 3. Linux Ubuntu 22.04		1. Windows 10 IoT Enterprise LTSC 21H2 (64bit) ready 2. Linux Ubuntu 18.04
TPM & vPro	1. Intel vPro (i5/i7 CPU only) 2. S/W TPM 2.0 (BIOS)	S/W TPM 2.0 (BIOS)	1. Intel vPro (i5 CPU only) 2. S/W TPM 2.0 (BIOS)
Power Adaptor	AC-In 100~240V / DC-Out 12V, 90W		AC-In 100~240V / DC-Out 12V, 65W / 90W
Reliability	System operating temperature: 0~40°C / 32~104°F System humidity: 15% ~ 80% Storage temperature: -20~60°C / -4~140°F		
Dimensions (Wx Hx D)	392 x 321 x 201 mm / 15.43 x 12.67 x 7.87 in		
Weight	6.2 kg / 13.67 lb		

*Specification is subject to change without prior notice

Contact US

Partner Tech USA Inc.
 1255 N. Patt Street
 Anaheim, CA 92801
 Phone: 949-598-1888
sales@partnertechcorp.com

Partner Tech Mexico & Latin America
 Blvd. Palmas Hills 1, Piso 8, Valle de las Palmas, Huixquilucan
 Ciudad de México, 52764, Mexico
 Phone: 949-598-1888
info@partnertechcorp.com

