Printer

RP-630 High-Performance Thermal Printer



ENERGY STAR









FEATURES

- 58–80 mm / 2.25–3.15 in paper width
- 203 dpi x 180 dpi resolution
- 250 mm/s high-speed printing
- Triple interfaces: USB + serial + Ethernet
- Windows, macOS, Linux (CUPS), OPOS, JavaPOS
- ENERGY STAR® certified
- Optional water spill-proof cover
- Optional power adaptor cover

Printer

Specifications

Item		RP-630
Printing	Method	direct thermal
	Paper Loading	top
	Speed	250 mm/s or 9.8 in/s
	Width	58–80 mm / 2.28–3.15 in
	Resolution	203 dpi x 180 dpi
Paper	Type	Thermal paper
	Width	57.5 / 82.5 mm or 2.26 / 3.25 in
	Thickness	0.06 mm – 0.08 mm
	Roll Diameter	max 83 mm / 3.27 in
	Roll Core Inner	12.5 mm (± 0.5 mm) / 0.49 in
Memory		RAM: 2MB, Flash: 4MB
Reliability	TPH Life	150 km
	MCBF	60,000,000 lines
Auto Cutter		1,500,000 cuts
Sensors		Paper End, Cover Open, Black Mark
Interfaces		USB + serial + Ethernet
Emulation		ESC/POS command compatible
Driver		Windows, macOS, Linux (CUPS), OPOS, JavaPOS
Power	Type	external adaptor
	AC	100–240 VAC, 50/60 Hz
	DC	24 V DC, 2.15 A
Temperature	Temperature	operating: 5°C–45°C / 41°F–113°F
	Dimension	storage -40°C–60°C/ -40°F–140°
Dimensions		200 × 145 × 145 mm / 7.87 x 5.71 x 5.71 in (L x W x H)
Weight		1.45 kg / 3.2 lb
Color		black
Certificates		FCC, CE, CB, 3C, ENERGY STAR®, VCCI

*Specification is subject to change without prior notice

Contact US

Partner Tech Americas HQ
1255 N. Patt Street
Anaheim, CA 92801
Phone: +1 949 598 1888
sales@partnertechcorp.com

Partner Tech Mexico
5F, Av. Fundadores 935, Paseo de las Privanzas
C.P. 64750, Monterrey, Mexico
Phone: +52 55 9990 8274
sales@partnertechcorp.com