

# Printer

**RP-630**

**High-Performance Thermal Printer**



## FEATURES

- 58–80 mm paper width (2- and 3-inch)
- 203 dpi x 180 dpi resolution
- 250 mm/s high-speed printing
- Triple Interfaces: USB + Serial + Ethernet
- Windows, macOS, Linux (CUPS), OPOS, JavaPOS
- ENERGY STAR® certified
- Optional Water Spill-Proof Cover
- Optional Power Adaptor Cover

# Printer



## Specifications

Item		RP-630
Printing	Method	Direct thermal
	Paper Loading Scenario	Top
	Speed	250 mm/s
	Width	58–80 mm / 2.28"–3.15"
	Resolution	203 dpi x 180 dpi
Paper	Type	Thermal paper
	Width	57.5 / 82.5 mm 2.26" / 3.25"
	Thickness	0.06 mm ~ 0.08 mm
	Roll Diameter	Max 83 mm / 3.27
	Roll Core Inner	12.5 mm (± 0.5 mm) / 0.49"
Memory	RAM: 2MB, Flash: 4MB	
Reliability	TPH Life	150 km
	MCBF	60,000,000 lines
Auto Cutter	1,500,000 cuts	
Sensors	Paper End, Cover Open, Black Mark	
Interfaces	USB + Serial + Ethernet	
Emulation	ESC/POS Command Compatible	
Driver	Windows, macOS, Linux (CUPS), OPOS, JavaPOS	
Power	Type	External adaptor
	AC	100–240 VAC, 50/60 Hz
	DC	24 V DC, 2.15 A
Temperature	Temperature	Operating: 5°C–45°C / 41°F–113°F
	Dimension	Storage -40°C–60°C/ -40°F–140°
Dimensions	200 × 145 × 145 mm / 7.87 x 5.71 x 5.71in (L x W x H)	
Weight	1.45 kg / 3.2 lb	
Color	Black	
Certificates	FCC, CE, CB, 3C, ENERGY STAR®, VCCI	

\*Specification is subject to change without prior notice

## Contact US

**Partner Tech USA Inc.**  
1255 N. Patt Street  
Anaheim, CA 92801  
Phone: 949-598-1888  
sales@partnertechcorp.com

**Partner Tech Mexico & Latin America**  
Blvd. Palmas Hills 1, Piso 8, Valle de las Palmas, Huixquilucan  
Ciudad de México, 52764, Mexico  
Phone: 949-598-1888  
info@partnertechcorp.com

