

Paula

Kiosk



FEATURES

- Compact all-in-one self-order kiosk
- High-brightness PCAP multi-touch display (21.5" or 15.6")
- Adjustable viewing angle
- Integrated 2D barcode scanner and thermal printer
- LED status indicator
- ADA-pad compatible with JAWS for Kiosk accessibility
- Universal payment bracket



Paula

PARTNER

Self-Service Kiosk | Frictionless Self-ordering & Checkout



Increase Sales Capacity



Quick & Convenient



No Lines



Partner Tech Corporation

partnertechcorp.com

Paula



Specifications



Item	Paula Kiosk – Windows/Linux/Android		
Display / Touch Panel	21.5", 16:9, 1920 x 1080, 500 nits, PCAP touch, anti-glare 15.6", 16:9, 1920 x 1080, 400 nits, oTP touch, anti-glare (option) 15.6", 16:9, 1920 x 1080, 250 nits, PCAP Touch, anti-glare		
CPU	Alder Lake Intel Core i3-1215U Intel Core i5-1245U (vPro) Intel Core i7-1265U (vPro)	Elkhart Lake Intel Celeron J6412	Rockchip RK3399
Memory	DDR4: 8 GB / 16 GB / 32 GB		DDR4: 4 GB
Storage	M.2 PCIe SSD: 128 GB / 256 GB / 512 GB / 1TB		eMMC: 64 GB
I/O Ports	1 x Intel Gigabit Ethernet (host)	1 x Gigabit Ethernet (host)	
	1 x RJ45 Ethernet (EMV payment)	1 x RJ45 Ethernet (EMV payment)	
	1 x AC male power socket		
	2 x USB 2.0 (option)		
	1 x power switch button		
Speaker	1 x speaker 3W		
Printer	RP-700, Epson TM-m30 (option)		
Barcode Scanner	2D barcode scanner		
Peripherals (options)	LED status indicator (multi-color light bar)		
	Universal EMV terminal bracket		
	ANKER ADA-pad (assistive, audio-enabled keypad designed for easy menu navigation)		
Wi-Fi/BT (option)	Wi-Fi 6E Intel AX210 IEEE 802.11 a/b/g/n/acR2/axR2		Wi-Fi 5 IEEE 802.11 a/b/g/n/ac
	BT 5.3		BT 5.0
Operating System	Windows 11 IoT Enterprise LTSC 24H2 (64bit)		Android 14 GMS
	Windows 10 IoT Enterprise LTSC 21H2 (64bit)		
	Linux (Ubuntu 22.04)		
vPro & TPM (options)	Intel vPro (i5 /i7 only)	S/W TPM 2.0 (BIOS)	n/a
	SW TPM 2.0		
Software (option)	JAWS for Kiosk enables independent kiosk use for blind and low-vision customers through speech-guided navigation. Interacts with the ADA-pad.		
Power Adaptor	AC-In 100~240V / DC-Out 12V, 90W/120W		AC-In 100~240V / DC-Out 12V, 65W/90W
Reliability	System operating temperature: 5~40°C / 32~104°F		
	System humidity: 15% ~ 80%		
	Storage temperature: -20~60°C / -4~140°F		
Dimensions (W x H x D)	365 x 745 x 322.93 mm / 13.19 x 29.33 x 12.65 in		
Weight	21.5 kg / 47.4 lbs		

*Specification is subject to change without prior notice

Contact Now

TAIWAN E-mail:sales@partner.com.tw
USA E-mail:sales@partnertechcorp.com
EUROPE E-mail:info@partner-tech.eu
UK E-mail:sales@partnertechuk.com
CHINA E-mail:sales@partnertech.com.cn

MIDDLE EAST
JAPAN
AUSTRALIA
ASIA PACIFIC

E-mail:info@partnertechme.com
E-mail:sales-jp@partner.com.tw
E-mail:sales_au@partnertechapac.com
E-mail:sales@partnertechapac.com

