



## Specifications



Item	ALFA Mini	ALFA	ALFA Pro
CPU	Intel® Celeron® J6412 (Elkhart Lake) Intel® Core™ i3-1115G4 (Tiger Lake UP3) Intel® Core™ i5-1145G7, vPro (Tiger Lake UP3 ) Intel® Core™ i7-1185G7, vPro (Tiger Lake UP3 )		
Memory	DDR4: 4 GB / 8 GB / 16 GB / 32 GB		
Storage	M.2 PCIe SSD: 128 GB / 256 GB / 512 GB / 1 TB		
I/O Ports	3 x serial ports, RS-232 (DB9), 0V/5V/12V selected in BIOS (COM1, COM2, COM3)	4 x serial ports, RS-232 (DB9), 0V/5V/12V selected in BIOS (COM1, COM2, COM3, COM4)	
	1 x LAN (IEEE 802.3 10/100/1000 Mbps) 1 x Intel LAN (IEEE 802.3 10/100/1000 Mbps) – for Tiger Lake 1 x RJ11 port support for 2 cash drawers with 24V / 12V jumper setting 1 x DC + 12V out 2 x USB 3.2 + 6 x USB 2.0 4 x USB 3.2 + 4 x USB 2.0 – for Tiger Lake 1 x DC + 12V input 1 x audio (1 x line-out) 1 x HDMI 1 x Type-C (data transfer only) 1 x Type-C (data transfer+ display) – for Tiger Lake 1 x VGA		
Wireless Option	Wi-Fi 6E Intel AX210 (IEEE 802.11 a/b/g/n/acR2/axR2) / BT 5.3		
Power USB	N/A		3 x 12V & 1 x 24V powered USB
Display Support	2 independent displays (HDMI + VGA) 3 independent displays (HDMI + Type C + VGA) – for Tiger Lake		
Operating System	1. Windows 11 IoT Enterprise GAC (64bit) 2. Windows 10 IoT Enterprise LTSC 21H2 (64bit) and newer version 3. Ubuntu 22.04		
TPM & vPro	Intel vPro (i5/i7 CPU only) S/W TPM 2.0 (BIOS)		
Power Adaptor	AC-In 100~240V / DC-out 12V, 65W, 90W (Tiger Lake)		AC-In 100~240V / DC-out 12V, 180W
Reliability	System operating temperature: 0~40°C / 32~104°F System humidity: 15% ~ 80% Storage temperature: -20~60°C / -4~140°F		
Dimensions (Wx Hx D)	255 x 131.5 x 45.1 mm / 10.04 x 5.18 x 1.78 in	255 x 131.5 x 63.1 mm / 10.04 x 5.18 x 2.48 in	
Weight	1.5 kg / 3.3 lb	1.8 kg / 3.97 lb	
Warranty	5 years		

\*Specification is subject to change without prior notice

## Specifications



Item	ALFA Max	ALFA Max Pro
CPU	(Alder Lake-S) Intel® Core™ i3-12100T, H610 Chipset Intel® Core™ i5-12500T, Q670 Chipset, vPro Intel® Core™ i7-12700T, Q670 Chipset, vPro	
Memory	DDR4: 4 GB / 8 GB / 16GB / 32GB	
Storage	2.5" SATA SSD: 128 GB / 256 GB / 512 GB / 1 TB 2nd 2.5" SATA SSD (option)	
I/O Interface	2 x serial ports, RS-232 (DB9), 0V/5V/12V selected in BIOS (COM1, COM2) 2 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in BIOS (COM3, COM4) 2 x LAN(IEEE 802.3 10/100/1000 Mbps) 1 x RJ11 port support for 2 cash drawers with 24V / 12V jumper setting 1 x DC + 12V out 4 x USB 3.2 + 4 x USB 2.0 1 x DC + 12V input 1 x audio (1 x line-out) 1 x mic in 1 x HDMI 1 x VGA	
Wireless Option	Wi-Fi 6E Intel AX210 (IEEE 802.11 a/b/g/n/acR2/axR2) / BT 5.3	
Power USB	N/A	3 x 12V & 1 x 24V powered USB
Display Support	3 independent displays (HDMI + VGA + 2nd VGA)	
Operating System	1. Windows 11 IoT Enterprise LTSC 24H2 (64bit) 2. Windows 10 IoT Enterprise LTSC 21H2 (64bit) 3. Linux Ubuntu 22.04	
TPM & vPro	1. Intel vPro (i5/i7 CPU only) 2. S/W TPM 2.0 (BIOS) 3. RAID (Q670 chipset only)	
Power Adaptor	AC-In 100~240V / DC-Out 12V, 120W	AC-In 100~240V / DC-Out 12V, 180W
Reliability	System operating temperature: 0~40°C / 32~104°F System humidity: 15% ~ 80% Storage temperature: -20~60°C / -4~140°F	
Dimensions (Wx Hx D)	255 x 185 x 81.1 mm / 10.04 x 7.28 x 3.19 in	
Weight	3.5 kg / 7.11 lb	
Warranty	5 years	

\*Specification is subject to change without prior notice

## Contact US

**Partner Tech USA Inc.**  
1255 N. Patt Street  
Anaheim, CA 92801  
Phone: 949-598-1888  
sales@partnertechcorp.com

**Partner Tech Mexico & Latin America**  
Bld. Palmas Hills 1, Piso 8, Valle de las Palmas, Huixquilucan  
Ciudad de México, 52764, Mexico  
Phone: 949-598-1888  
info@partnertechcorp.com

