

CLEO

C10 Series**All-in-One Compact POS Terminal**

FEATURES

- Compact all-in-one design
- 10.1" PCAP touch display
- Embedded 3" thermal printer and payment peripherals
- Large selection easily accessible ports
- Concealed cables keep the counter clutter-free
- Optional Wi-Fi and BT connectivity

Specifications



Item	C10-1E		C10-1N	C10-1R (RK3576)
Display	10.1", 9:16, 800 x 1280 (250 nits)			
Touch	PCAP touch			
CPU	Elkhart Lake Intel® Celeron® J6412		Alder Lake-N Intel® Processor N97	RK3576 Quad Cortex-A72 + quad Cortex-a53 up to 2.3 GHz
Memory	DDR4 4GB, 8GB, 16GB, 32G		DDR4 4GB, 8GB, 16GB	DDR4 4GB
Storage	M.2 PCIe SSD: 128GB / 256GB / 512GB / 1TB		M.2 PCIe SSD: 128GB / 256GB / 512GB / 1TB	eMMC 64GB
I/O Interface	4 x serial ports, RS232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2, COM3, COM4)			2 x serial ports, RS232 (RJ45), 0V/5V/12V selected in UI (COM1, COM2) (option)
	1 x LAN (IEEE 802.3 10/100/1000 Mbps)		1 x LAN (IEEE 802.3 10/100/1000/ 2500 Mbps)	1 x LAN (IEEE 802.3 10/100/1000 Mbps)
	1 x HDMI			1 x HDMI + 1 x Type-C (data transfer only)
	4 x USB 3.2 + 2 x USB 2.0			
	1 x RJ11 port with support for 2 cash drawers with 24V / 12V jumper setting			
	1 x audio (1 x line-out)			
	1 x DC +24V input			
Printer	3" Thermal Printer			
Speaker	1 x speaker 3W			
Peripheral Options	MSR, EMV reader, Fingerprint reader, RFID / NFC reader, 2D barcode scanner, 8MP camera, USB 2nd display (CD-101, COCO)			
Wireless Option	Wi-Fi 6E Intel AX210 IEEE 802.11 a/b/g/n/acR2/axR2, BT5.3			WiFi6 : 2T2R 802.11 ax/ac/a/b/g/n Wi-Fi + BT 5.1 (on board)
Display Support	3 Independent displays (main display + HDMI + CD-101C/COCO)			2 independent displays (main display + CD-101C/COCO or HDMI)
Operating System	1. Windows 11 IoT Enterprise LTSC 24H2 (64bit)			Android 15 GMS
	2. Windows 10 IoT Enterprise LTSC 21H2 (64bit)			
	3. Ubuntu 22.04			
TPM & vPro	H/W TPM 2.0		S/W TPM 2.0 (BIOS)	NA
Power Adaptor	AC-In 100~240V / DC-Out 24V, 72W			
Reliability	System operating temperature: 0~40°C / 32~104°F			
	System humidity: 15% ~ 80%			
	Storage temperature: -20~60°C / -4~140°F			
Dimensions (Wx Hx D)	262.26 x 291.77 x 247.13 mm / 10.33 x 11.49 x 9.72 in			
Weight	3.3 Kg / 7.28 lb			

*Specification is subject to change without prior notice

Contact Now

TAIWAN E-mail:sales@partner.com.tw
USA E-mail:sales@partnertechcorp.com
EUROPE E-mail:info@partner-tech.eu
UK E-mail:sales@partnertechuk.com
CHINA E-mail:sales@partnertech.com.cn

MIDDLE EAST
JAPAN
AUSTRALIA
ASIA PACIFIC

E-mail:info@partnertechme.com
 E-mail:sales-jp@partner.com.tw
 E-mail:sales_au@partnertechapac.com
 E-mail:sales@partnertechapac.com

