

SUNMI L2K

- 2GB RAM+16GB ROM
- Increased expansion options support multiple accessories
- The industry-grade touch screen comes with a glove mode option
- Compatible with Honeywell/Zerba 1D and 2D barcode scanners
- Built-in small battery allows for replacement of the main battery without needing to turn off the mobile computer
- With this UHF trigger handle, SUNMI L2K can enhance your work efficiency by enabling the reading of multiple RFID tags.



1.5W
loudspeaker



IP65
rating



1.5M
drop proof



SUNMI L2K
Charging Base (optional)



SUNMI L2K
UHF Trigger Handle (optional)

SUNMI L2K Technical specifications

OS Android 7.1 SUNMI OS	CPU Qualcomm Snapdragon quad-core 1.4GHz	Memory 16GB ROM+2GB RAM	Display 4" WVGA 800x480,IPS Multi touch, Support glove mode	Adapter Input:Type-C Output:DC 5V/2A
Wi-Fi 2.4G/5G Support IEEE 802.11 a/b/ g/n	Bluetooth Support BLE Support Bluetooth 2.1/ 3.0/4.2	Voice and Audio 1.5W Two mic	Port 1x Type-C USB Support OTG Support pogo pin	Key Power button Volume up/down Scan button 20 physical keys
Battery Removable polymer Lithium battery 3.8V/5000mAh	Communication 2G/3G/4G	1D/2D Scanner Zebra 2D scanner Honeywell(Optional)	Camera Rear: 13MP autofocus Front: 2MP fixedfocus	NFC ISO 14443 Type A/B FeliCa and ISO 15693 cards
GPS Support AGPS Support GPS/Glonass/Beidou	SIM Card Slot SIMx1 PSAMx1 Support 1.8V/3.0V	Size 159.4*73*19mm	Environmental Operating temperature:-20°C-55°C Storage temperature:-40°C-70°C Sealing:IP65 Drop Specification:1.5m	

Optional



Trigger Handle
Support barcode reading



UHF Trigger Handle
Support RFID tag reading



Charging Base
Support L2K and UHF charging

SUNMI L2K UHF Trigger Handle Technical specifications

RFID Engine Impinj Indy R2000	Fastest Read Rate >200 tags/sec	Longest Read Range >10m	Antenna Circularly polarized (4dBi)	Battery 3.6V/3350mAh
Protocols & Standards EPC Global UHF Class 1 Gen 2 / ISO 18000-6C/ ISO 18000-6B	Frequency Range Chinese mainland 920-925MHz American standard 902-928 MHz European standard 865-868 MHz	Environmental Operating temperature:-10°C-50°C Storage temperature:-40°C-70°C Sealing:IP65 Drop Specification:1.5m		

Partner Tech Middle East FZCO is now Distributing Sunmi Technology



Office No. 1004, 10th Floor, Aspect Tower, 33a Happiness Street, Business Bay, Dubai, UAE



+971 4 447 4273



sales@partnertechme.com



ae.partnertechcorp.com