SUNMI T2s LITE Desktop POS

Flexible forms bring abundant experience

Performance breakthroughs on your fingertips.

High performance octa-core processor, up to 2.2Ghz. Equipped with large-capacity memory of 3GB RAM + 32GB ROM, T2s LITE allows you to experience unparalleled operation smoothness.

Anti-interference touch screen.


To realize your demand on worry-free touch experience in various environments, even near high-power devices, we employ an industrial-grade touch chip which is more resistant to EMI.

Unlock more possibilities with a VESA mount.

T2s LITE can be mounted with a VESA mount, enabling more applicable scenarios. For example, it can be used as a kitchen display of a KDS, greatly improving the restaurant operational efficiency.



Optional Accessories






VESA mount

For more space-saving installation and more flexible use.





15.6" Main: 15.6" FHD, 1920*1080



15.6" +10.1" Main: 15.6" FHD, 1920*1080 Second: 10.1" HD, 1024*600



15.6" +15.6" Main: 15.6" FHD, 1920*1080 Second: 15.6" FHD, 1920*1080



T2s LITE Tech Specs


Model Approved Config 1: L1571 (Single-Display Version) Config 2: L1572 (Dual-Display (small + big) Version) Config 3: L1573 (Dual-Display (big + big) Version)		OS Android 9.0 SUNMI OS	CPU Kryo-260, Octa-core up to 2.2GHz	Memory 32GB ROM + 3GB RAM 64GB ROM + 4GB RAM (optional)
Camera Face Recognition camera or normal camera (only for configuraion 2&3)	Display Configuration 1: Main: 15.6" FHD, 1920*1080 Capacitive multitouch screen Configuration 2: Main: 15.6" FHD, 1920*1080 Capacitive multitouch screen Second: 10.1" HD, 1024*600 Capacitive multitouch screen Configuration 3: Main: 15.6" FHD, 1920*1080 Capacitive multitouch screen Second: 15.6" FHD, 1920*1080 Capacitive multitouch screen			Speaker 1* 1.2W
Bluetooth BT2.1/3.0/4.0/5.0 BLE	Buttons 1* power button 2* volumn button	External Storage Card Support Micro SD (TF) Up to 64GB		SIM Card Slot 1* Micro SIM (optional)
LAN LAN 100M	Network 2G&3G&4G (optional)	Wi-Fi 2.4G/5.0GHz IEEE 802.11 a/b/g/n /ac	Interface 5* USB TypeA 1* RJ11 Serial port 1* RJ12 Cash drawer port 1* RJ45 LAN port 1* Audio jack 1* Power port 1* Micro-USB (debug)	Power Adapter Input: AC100 ~ 240V/1.5A Output: DC24V/1.5A
Dimensions 430*382*215mm (max)	Weight Configuration 1: 4.5 Kg Configuration 2: 5.1 Kg	Environment Operating temperature: 0°C ~ 40°C Storage temperature: -20°C ~ 60°C		

Partner Tech Middle East FZCO is Distributing Sunmi Technology



+971 4 447 4273

Configuration 3: 6.8 Kg



Office No. 1004, 10th Floor, Aspect Tower, 33a Happiness Street, Business Bay, Dubai, UAE

