

AD-215-S

21.5" Self-Checkout Kiosk



Maximize speed and convenience at the checkout with the AD-215-S self-checkout kiosk for a grab-and-go shopping experience. Ideal for use in high-volume retail environments such as convenience, drug, specialty, liquor, and hardware stores.

Multiple Payment Options

Easy and quick payment with support for debit and credit cards, contactless and mobile payments.

Receipt & Coupon Printing

Integrated and lockable 3-inch thermal printer for high-speed printing of receipts and coupons.

Speed & Efficiency

Offer the convenience of self-checkout with less waiting in line

Increase Profits

Add extra checkouts without hiring more staff and leverage automated cross-sale and upsale programs to boost revenue.

SPECIAL FEATURES

- 21.5" PCAP touch screen with full HD resolution
- High performance Intel or Rockchip processor
- Fanless design
- Powerful vertical slot scanner with omnidirectional 1D and 2D scanning capability

OPTIONS

- Wi-Fi module
- ADA keypad
- RFID reader
- 5MP camera
- Led indicator
- Wheels kit

AD-215-S

Product configuration



Durable Bagging Area

110 lb/ 50 kgs weight capacity on each side



AD-215-S

| Item | AD-215-S | | |
|------------------------|---|--------------------------------------|--|
| Display | 21.5" Resolution 1920x1080 (300 nits) | | |
| Touch | PCAP touch | | |
| CPU | Intel® Core™ i3-7100U (Kaby Lake) Intel® Core™ i5-7300U (Kaby Lake) | Intel Celeron J3455 (Apollo Lake) | Rockchip RK3399 |
| Memory | DDR4 4GB, 8GB, 16GB | DDR3L 4GB, 8GB | LDDR4 4GB |
| Storage | M.2 PCIe SSD: 128G / 256G | M.2 SATA SSD: 128G / 256G | eMMC32GB + 1x Micro SD Card Slot (up to 128GB) |
| External I/O Interface | 2 x Serial Ports, RS-232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2) | | |
| | 2 x LAN, (IEEE 802.3 10/100/1000 Mbps Ethernet, RJ45) | | 1 x LAN, (IEEE 802.3 10/100/1000 Mbps Ethernet, RJ45) |
| | 1 x RJ11 port with support for two cash drawers with 24V / 12V jumper setting | | |
| | 1 x DC+12V output | | |
| | 4 x USB 3.0 (USB3.0/2.0) | | 1 x USB3.0 (OTG) + 5 x USB2.0 |
| | 1 x DC +12V input | | |
| | 1 x Audio (1 x line out) | | |
| | 1 x HDMI | | |
| | 1 x VGA | | 1 x Micro SD card |
| | Speaker | 1 x Speaker (3W) | |
| Printer | 3" Thermal Printer | | |
| Barcode Scanner | 2D Barcode Scanner | | |
| Optional Peripheral | MSR, EMV Reader, Fingerprint Reader, RFID Reader | | |
| | EMV Terminal Bracket | | |
| | 5MP Camera | | |
| | UVC Light | | |
| | ADA Keypad | | |
| | Wheels Kit (2 wheels, 1 handle) | | |
| WIFI/BT(option) | 2.4GHz/5GHz (IEEE 802.11a/b/g/n/ac), BT 4.2 (supports BLE) | | |
| Display Support | 3 Independent Displays (Main Display + HDMI + VGA) | | 2 Independent Displays (Main Display + USB or HDMI) |
| Spill & Dust resistant | N/A | | |
| Operation System | 1. Windows 10 IoT Enterprise (64bit) | 1. Windows 10 IoT Enterprise (64bit) | 1. Android 9.0 |
| | 2. Linux (Ubuntu 18.04) | 2. Linux (Ubuntu 18.04) | 2. Android 11 |
| | 3. Debian 9.12 x64 (Kernel 4.9.x) | 3. CentOS 7.8 x64 | |
| | | 4. Debian 9.12 x64 (Kernel 4.9.x) | |
| Software | 1. Intel V-Pro (i5 CPU only) | S/W TPM 2.0 (BIOS) | N/A |
| | 2. S/W TPM 2.0 (BIOS) | | |
| Power Adaptor | AC-In 100~240V / DC-Out 12V, 120W | | AC-In 100~240V / DC-Out 12V, 90W |
| Reliability | System Operating Temperature: 41~104°F/ 5~40°C | | |
| | System Humidity: 15% ~ 80% | | |
| | Storage Temperature: -4~140°F/ -20~60°C | | |
| Dimensions | 38.78 (W) x 65.75 (H) x 18.52 (D) in/ 985 (W) x 1670 (H) x 470.5 (D) mm | | |

*Specification is subject to change without prior notice



CARE . TRUST . RESPONSIBILITY

TAIWAN E-mail:sales@partner.com.tw
 USA E-mail:sales@partnertechcorp.com
 EUROPE E-mail:info@partner-tech.eu
 UK E-mail:sales@partnertechuk.com
 CHINA E-mail:sales@partnertech.com.cn

MIDDLE EAST E-mail:info@partnertechme.com
 AUSTRALIA E-mail:sales@partner-tech.com.au
 SOUTH EAST ASIA E-mail:ptse@partner.com.tw
 JAPAN E-mail:sales-jp@partner.com.tw