

SP-5514

SP-5514

All-in-one Touch Screen POS



FEATURES

- Flexible modular design and customer display / 2nd monitor support
- Bezel-free 14" screen with projected capacitive touch (multi-touch)
- Dust-and spray-resistant front panel (IP65)
- Multiple I/O configurations available
- Maintenance and Service Friendly Design



SP-5514



Specifications



Item	SP-5514
Size	15"
Aspect Ratio	4:3
Resolution	1024 x 768
Brightness (typical)	220 nits
Touch	PCAP Touch
CPU	Intel® Celeron® J1900 (Bay Trail)
Memory	DDR3L 4GB, 8GB
Storage	1 x 2.5" SATA HDD or 1 x 2.5" SATA SSD
External I/O Interface	2 x Serial Ports, RS232 (DB9), 0V/5V/12V selected by jumper setting (COM1, COM2) 1 x LAN (IEEE 802.3 10/100/1000 Mbps Ethernet, RJ45) 1 x RJ11 port supports 2 cash drawer with 24V / 12V by jumper setting 1 x DC + out 12V 1 x USB 3.0 + 3 x USB 2.0 1 x DC +12V input 1 x Audio (1 x line-out) 1 x VGA
Speaker	1 x Speaker (3W)
Optional Peripheral	MSR, IC Card Reader, Fingerprint, RFID, i-Button, VFD, USB 2nd Display, VGA 2nd Display
Wireless (option)	Wi-Fi 6E Intel AX210 IEEE 802.11 a/b/g/n/acR2/axR2, BT5.2
Display Support	2 Independent Displays (Main Display + VGA)
Spill & Dust Resistant	IP54 Certified
Operation System	1. Windows 10 IoT Enterprise 21H2 LTSC (64bit) 2. Ubuntu 16.04
Power Supply	AC-In 100~240V / DC-Out 12V, 65W, 90W
Reliability	System Operating Temperature: 0~40°C / 32~104°F System Humidity: 15% ~ 80% Storage Temperature: -20~60°C / -4~140°F
Dimensions (Wx Hx D)	369 x 302 x 251 mm / 14.53 x 11.89 x 9.88 inch
Weight	5 kgs / 11.02 lbs

*Specification is subject to change without prior notice

Contact Now

TAIWAN E-mail:sales@partner.com.tw
USA E-mail:sales@partnertechcorp.com
EUROPE E-mail:info@partner-tech.eu
UK E-mail:sales@partnertechuk.com
CHINA E-mail:sales@partnertech.com.cn

MIDDLE EAST E-mail:info@partnertechme.com
AUSTRALIA E-mail:sales@partner-tech.com.au
SOUTH EAST ASIA E-mail:ptse@partner.com.tw
JAPAN E-mail:sales-jp@partner.com.tw

